

Hybridní CCTV síťové rekordéry

iCATCH

RMH x28



VLASTNOSTI

- Připojení až 4MPx (2688x1520) CCTV kamer
- Podpora AHD, TVI, CVI analogových a IP kamer
- Umožňuje nastavení OSD menu po koaxiálním kabelu (UTC)
- Podpora IP kamer s Onvif Profile protokol (V2.4)
- Obsahuje funkci redundantního nahrávání
- Výborná kvalita obrazu








KELCOM INTERNATIONAL 

MADE IN TAIWAN   



www.kelcom.cz

RMH x28

Model		RMH-0428EU-K x28	RMH-0428MU-J x28	RMH-0828EU-K x28	RMH-0828MU-J x28	RMH-1628EU-K x28	RMH-1628EU-N x28	RMH-1628AU-N x28
Picture								
Camera Input		4CH XVI Universal Hybrid		8CH XVI Universal Hybrid		16CH XVI Universal Hybrid		
Housing		K	J	K	J	K	N	
Analog Live Input		TVI/AHD/CVI : 4MP @ 15 fps, 3MP @ 18 fps, 1080P @ 30/25 fps, 720P @ 30/25 fps, 960H / D1 @ 30/25fps						
Video	Network Input	Bandwidth (1 person login-in from remote)	Max. 40Mbps (Max. Main stream: 6 Mbps + Sub stream: 1 Mbps per channel)		Max. 50Mbps (Max. Main stream: 6Mbps + Sub stream: 1Mbps per channel)		Max. 115Mbps (Max. Main stream: 6Mbps + Sub stream: 1Mbps per channel)	
		Single Live & Playback channel (without Analog camera input)	Max. 4MP · 3MP · 1080P@30/25 fps (ONVIF 2.4)		Max. 4MP · 3MP · 1080P@30/25 fps (ONVIF 2.4)		Max. 4MP · 3MP · 1080P@30/25 fps (ONVIF 2.4)	
		Multiple Live & Playback channels (without Analog camera input)	VGA@ 4 x 30/25 fps		VGA@ 8 x 30/25 fps		VGA@ 16 x 30/25 fps	
Output		1 HDMI with Audio and 1 VGA (Max. 1920x1080) 1 Main BNC		1 HDMI with Audio and 1 VGA (Max. 1920x1080) 1 Main BNC		1 HDMI (Max. 3840 x 2160) with Audio and 1 VGA (Max. 1920x1080) 1 Main BNC		
Audio	Input	1	4	1	4	1	16	
	Compression	Audio Codec : G726 · G711 u/a IMA_ADPCM Sample Rate : 8k, Channel 1 Depth 16						
	Output	1	2	1	2	1	2	
Operating System		Embedded Linux OS						
System	SATA Devices	Max. 1 x SATA Device (HDD x 1)		Max. 1 x SATA Device (HDD x 1)		Max. 1 x SATA Device (HDD x 1)	Max. 3 x SATA Devices (HDDx2, HDDx2+Optical Device x1)	Max. 4 x SATA Devices(HDDx3+eSATAx1, HDDx2+Optical Device x1+eSATAx1)
	External HDD	N/A		N/A		N/A		
	Alarm In / Relay Out	N/A	Alarm-in x 4 Relay-out x 1	N/A	Alarm-in x 4 Relay-out x 1	N/A		Alarm-in x 16 Relay-out x 2
	Serial Interface	RS-485						
	USB Ports	USB2.0 X2						
Dimension (mm)		280(w)x51(h)x203(d)		280(w)x51(h)x203(d)		280(w)x51(h)x203(d)	430(w)x55(h)x293(d)	
Display	Power Rating	12V 2A, 24W		12V 2A, 24W		12V 3A, 36W	12V 5A, 60W	12V 5.83A, 70W
	Split Screen	1,4, SEQ.		1,4, 8, SEQ.		1, 4, 9, 13, 16,SEQ.		
	Auto Channel Switching	Switching time : 1 ~ 99 sec						
Mode		Zoom, Auto SEQ.						
Compression		H.264 High Profile						
Recording	Main (Recording) Resolution	2592 x 1944, 2592 x 1520, 2018 x 1524, 1920 x 1080, 1280 x 720, 944 x 480, 704 x 480, 352 x 240 (NTSC) / 944 x 576, 704 x 576, 352 x 288 (PAL)						
	Sub (Network) Resolution	640 x 360 / 352 x 240, 176 x 120 (NTSC) / 352 x 288, 176 x 144 (PAL)						
	Picture Quality	10~100 levels for adjustment						
	Mode	Continuous, Event, Schedule						
	Record Rate	TVI/AHD/CVI :4MP @ 7/6 fps, 3MP @ 10/8 fps, 1080P @ 15/12 fps, 720P @ 30/25 fps, 960H / D1 @ 30/25 fps						
Playback	Pre-Alarm	1 ~ 5 SEC						
	Post-Alarm	1 ~ 100 SEC						
	Search Mode	Date/time, Event						
Zoom		*Digital (x2 ~ x5)						
Network	Network Interface	10/100 Ethernet		10/100 Ethernet		10/100/1000 Ethernet		
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS						
	Application	Windows 7 , 8, 8.1, 10 Mac OS X						
	Remote Software	SoCatch, IE Browser, iCMS Pro						
Backup	Account	1 Admin + 10 Users						
	Mobile Device	Windows Phone 7.8, 8.1,10 iPhone, iPad, Android						
	Interface	USB or SATA						
Alarm	Audio Backup	YES						
	Backup Type	Network, ext. USB flash device , SATA optical DVD..etc.						
	Motion Detection	Sensitivity: 100 levels for each channel Area: Programmable individually						
OSD & DVR Control	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)						
	Multi-Language	Supported						
	Camera Title	Multi-Language						
	USB Mouse	YES						
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)						
	Remote Controller	IR Remote Control						
	System Upgrade	USB Flash Drive, iWatch DVR						
General	Pan/Tilt/Zoom Control	Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)						
	Operating Temperature	0°C ~ +55°C (32°F ~ 131°F)						
Operating Humidity		10%~80%						

All specifications are subject to change without notice.



Kelcom International spol. s r. o.

Tomkova 142

500 02 Hradec Králové

tel. +420 495 513 886

e-mail: obchod@kelcom.cz